


HIGHWAY

Solar Module

HT60-156M

-270W/275W/280W/285W/290W



TUV certification



Higher module's output power



HT-SAAE guarantees highest production standards: IEC 61215, IEC 61730, IEC 62716 (Ammonia corrosion) & IEC 61701 (Salt Mist Corrosion)



PID (potential induced degradation) Resistant



All HT modules are double EL tested avoiding invisible cracks, dark cells and broken bars to ensure the performance, quality and reliability.



All the modules are sorted and packaged by amperage, reducing mismatch losses and maximizing system output.



Products Warranty



Warranty on power output



Strict quality control, meeting the highest international standards: ISO 9001, ISO14001 and OHSAS18001



Guaranteed positive tolerance 0/+5w ensures power output reliability



Electrical Characteristics

Module	HT60-156M				
Maximum Power at STC(Pmax)	270W	275W	280W	285W	290W
Open-Circuit Voltage(Voc)	38.2V	38.4V	38.6V	38.8V	39.0V
Optimum Operating Voltage (Vmp)	31.6V	32.0V	32.4V	32.8V	32.2V
Short-Circuit Current(Isc)	9.18A	9.25A	9.32A	9.39A	9.49A
Optimum Operating Current(Imp)	8.55A	8.61A	8.65A	8.70A	9.01A
Module Efficiency	16.6%	16.9%	17.2%	17.5%	17.8%
Power Tolerance	0 ~ +5W				
Maximum System Voltage	1000V/1500V DC (IEC) / 600V DC(UL)				
Maximum Series Fuse Rating	15A				
Operating Temperature	-40 °C to +85 °C				
STC: Irradiance 1000W/m ² , module temperature 25, AM=1.5					
Optional black frame or white frame module according to customer requirements					

NOCT

Module	HT60-156M				
Maximum Power	197W	201W	205W	209W	213W
Open Circuit Voltage (Voc)	34.6V	34.8V	35.0V	35.2V	35.4V
Maximum Power Voltage (Vmp)	28.6V	29.0V	29.4V	29.8V	29.3V
Short Circuit Current (Isc)	7.41A	7.46A	7.51A	7.58A	7.67A
Maximum Circuit Current (Imp)	6.90A	6.94A	6.98A	7.03A	7.28A
NOCT	45 °C ± 2 °C				
NOCT: Irradiance 800W/m ² , ambient temperature 20 °C, wind speed 1 m/s					

Mechanical Characteristics

Solar Cells	Monocrystalline 156 × 156mm	
No. of Cells	60 (6 × 10)	
Dimensions	1640mm×992mm×35mm(64.6×39×1.4in)	
Weight	18.5kg (40.8lbs)	
Front Glass	High transmission tempered glass	
Frame	Anodized aluminium alloy	
Junction Box	IP67	
Cable	4mm ² (IEC)/12AWG(UL), 900mm	
Connectors	MC4/MC4 Comparable	
Module Pieces per Container (40' High Cube Container)	784pcs	




Temperature Characteristics

Temperature Coefficient of Pmax	γ (Pm)	-0.41%/K
Temperature Coefficient of Voc	β (Voc)	-0.34%/K
Temperature Coefficient of Isc	α (Isc)	0.049%/K

Warranty

10-year product warranty	
25-year warranty on power output	
Specific information is referred to the product quality guarantee	

Information Box



I-V Curves

Shanghai Aerospace Automobile Electromechanical Co., Ltd.
website: www.ht-saae.com
Email: pvmarketing@ht-saae.com

Factory: Lianyungang ShenZhou New Energy Co., Ltd.