




Product Service

CERTIFICATE

No. Z2 086674 0007 Rev. 02

Holder of Certificate: **Shanghai Aerospace Automobile Electromechanical Co., Ltd.**
222 Caoxi Rd, the 8th Floor of Spaceflight Building
200235 Shanghai
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono & Poly-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704061913215-02

Valid until: 2026-08-09

Date, 2021-08-11

(Zhulin Zhang)

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

CERTIFICATE

No. Z2 086674 0007 Rev. 02

Model(s):

Poly series:

HT72-156P-xxx (xxx=320-360, in step of 5);
 HT60-156P-xxx (xxx=265-300, in step of 5);
 HT50-156P-xxx (xxx=220-250, in step of 5);
 HT48-156P-xxx (xxx=210-240, in step of 5);
 HT72-156P-M-xxx (xxx=310-330, in step of 5);
 HT60-156P-M-xxx (xxx=260-275, in step of 5);
 HT50-156P-M-xxx (xxx=215-225, in step of 5);
 HT48-156P-M-xxx (xxx=210-220, in step of 5);
 HT72-156P-MC-xxx (xxx=315-340, in step of 5);
 HT60-156P-MC-xxx (xxx=265-280, in step of 5);
 HT72-156P-C-xxx (xxx=325-365, in step of 5);
 HT60-156P-C-xxx (xxx=270-300, in step of 5);

Mono series:

HT72-156M-xxx (xxx=340-405, in step of 5);
 HT60-156M-xxx (xxx=285-335, in step of 5);
 HT50-156M-xxx (xxx=235-280, in step of 5);
 HT48-156M-xxx (xxx=225-270, in step of 5);
 HT72-156M-M-xxx (xxx=355-410, in step of 5);
 HT60-156M-M-xxx (xxx=300-340, in step of 5);
 HT50-156M-M-xxx (xxx=250-280, in step of 5);
 HT48-156M-M-xxx (xxx=240-270, in step of 5);
 HT72-156M-MC-xxx (xxx=350-415, in step of 5);
 HT60-156M-MC-xxx (xxx=295-345, in step of 5);
 HT72-156M-C-xxx (xxx=350-410, in step of 5);
 HT60-156M-C-xxx (xxx=290-340, in step of 5);
 HT72-166M-xxx (xxx=410-475, in step of 5);
 HT66-166M-xxx (xxx=380-435, in step of 5);
 HT60-166M-xxx (xxx=345-395, in step of 5);
 HT48-166M-xxx (xxx=275-315, in step of 5);
 HT32-166M-xxx (xxx=185-210, in step of 5);
 HT30-166M-xxx (xxx=175-195, in step of 5);
 HT78-18X-xxx (xxx=560-610, in step of 5);
 HT72-18X-xxx (xxx=520-560, in step of 5);
 HT66-18X-xxx (xxx=475-515, in step of 5);
 HT60-18X-xxx (xxx=435-465, in step of 5);
 HT54-18X-xxx (xxx=390-420, in step of 5);
 HT36-18X-xxx (xxx=260-280, in step of 5);
 HT32-18X-xxx (xxx=230-250, in step of 5);
 HT30-18X-xxx (xxx=220-230, in step of 5);
 HT20-18X-xxx (xxx=145-155, in step of 5);
 HT16-18X-xxx (xxx=115-125, in step of 5).

xxx is standing for rated output power at STC



CERTIFICATE

No. Z2 086674 0007 Rev. 02

Parameters:

Safety Class:	Class II
Max. System Voltage:	1500V DC
Construction:	Framed, with Junction box, cable and connector.
Fire Safety Class:	Class C according to UL790
Severity of	
Salt Mist Test:	Level 6

Tested according to:

IEC 61215-1(ed.1)
 IEC 61215-1-1(ed.1)
 IEC 61215-2(ed.1)
 IEC 61730-1(ed.2)
 IEC 61730-2(ed.2)
 IEC 61701(ed.2)